

Safety Eyewash

Kestrel Court Harbour Road Portishead Bristol BS20 7AN

Phone: 01275 400456

Web: https://www.safety-eyewash.co.uk Email: sales@safety-eyewash.co.uk

Emergency Drench Hose With Twin Head



Product Code: S0406

Our twin head wall mounted drench hoses are the ideal addition to standard eyewash and safety shower facilities.

Model S0406 complies with the ANSI Z358.1-2014 standard for both an eyewash and drench hose. This dual use model can be used as either a fixed eyewash if left in its wall holder, or removed from the holder to be used as a drench hose.

The drench hoses provide a source of emergency water which can be directed to the area most affected, this is ideal where the injured person may not be able to stand at a traditional eve wash unit, or has collapsed.

The twin head emergency drench hoses are ideal for use in factories, chemical plants, foundries, workshops, and any workplace that requires emergency eye wash facilities. The hi-viz yellow detailing make them easily visible, and a simple design makes them easy to operate.

The twin head emergency drench hose is mounted on a yellow galvanised steel wall bracket, with two ABS yellow plastic eye/face wash spray heads with flip up dust covers, stay-open valve with squeeze lever and a 2438 mm reinforced yellow PVC hose.

ANSI Z358.1 – 2014 states that drench hoses can be used as supplements, but do not replace other types of emergency equipment.

Delivery

From stock 1 to 2 working days delivery time

Orders placed before 11.30am will be despatched for delivery next working day, or two working days if ordered after 11.30am

Tech specs

Spray head: twin yellow ABS plastic spray heads with flip open dust covers

Valve: Chrome plated brass stay-open valve with a locking clip and a stainless steel lever

Hose: 2438mm yellow PVC hose with a maximum working pressure of 300 psi

Wall bracket: yellow powder coated galvanized steel

Water Supply: 3/8" NPT male threaded, chrome plated brass swivel inlet with 1/2" adaptor

Water pressure: 2.07 - 6.21 bar Flow Rate: 11.73 litres per minute

Extras

There are currently no extras for the drench hoses

What is ANSI compliance?

The ANSI (or American National Standards Institute) is a nonprofit organisation that administers standards for products, processes and systems in the United States and around the world.

With regards to safety eye washing, the ANSI sets standards for water temperature and flow rate, as well as location and maintenance requirements. Our safety wall mounted eye washing pods conform to ANSI Z358.1-2009.

Related products

We also sell wall mounted eyewash fountains, as well as portable eye wash stations for use in remote areas without access to clean water.

In addition to eye wash fountains, we also provide a full range of safety showers.

**All pictures shown are for illustration purpose only and may be subject to change without notice. Actual product may vary due to product enhancement.

All dimensions shown are for guidance only and may be subject to change or alteration without notice. All items manufactured or purchased separately from a third party to fit our products should be checked against the actual dimensions of the physical product before purchase. We will not be liable for third party costs and consequential loss associated with the items not fitting third party components.**